




Aprisa XE delivers 106km cross-equator link between mountain and forest

When oil company Andes Petroleum Ecuador (ANDESPETRO) needed to deliver guaranteed telecommunications connectivity between two points over 100 kilometres apart, they selected 4RF Communications and the Aprisa XE. The use of sub 3 GHz spectrum overcame the propagation problems encountered in areas of forest, mountains and tropical environments, to provide 99.999% availability, with an E1 and Ethernet communications between the two locations.



APPLICATION AND DEPLOYMENT REQUIREMENTS

The main requirement for this application was to deploy a communications solution that would provide a guaranteed E1, G.703 service. Given the mountain and forest terrain and lack of existing communications infrastructure, radio was the clear solution. However, the distance between the mountain location and forest location severely limited the choices available to ANDESPETRO.

Initially a 5.8 GHz Spread Spectrum TDM over IP radio was proposed. As well as needing an external multiplexer to convert between IP and E1, this solution was unable to cope with the signal fading due to distance, forcing constant resynchronisation and degrading overall performance.

Another option considered was higher frequency microwave at 7 GHz. However, this option would not have been able to cover the required linking distance without a complex and expensive space diversity configuration and very large antennas.

Case study

ANDESPETRO

Ecuador




About ANDESPETRO

Andes Petroleum Ecuador Ltd. operates in the Tarapoa Block and the Lago Agrio Storage and Transfer Station in the province of Sucumbios. The hydrocarbons exploited are found in the "Ecuadorian Oriente Basin", an area depicting the complex history of Ecuador's geological evolution in the stratigraphic and structural traps of the Tena, Napo and Hollin formations.

NETWORK DEPLOYMENT

The Aprisa XE in the 1.5 GHz licensed spectrum band was chosen for the challenging long distance link: the use of the low frequency band meant reduced path loss and immunity to the environmental effects that impact higher frequency bands. Lower frequency bands also meant that small, lightweight grid-style antennas can be used. 4RF and its local partner, DIT Telecomunicaciones, carried out the required path planning to demonstrate that the link could meet both the distance and quality of service requirements.

The link was deployed in a 1.75 MHz channel using QPSK modulation, with a QJET interface card to support the E1 requirement. The link reflected the path planning activities that had been carried out, with a received signal of -59 dBm, with a very healthy fade margin.



ANDESPETRO link details				
Frequency (MHz)	= 1500.0; K = 1.33, 1.00; %F1 :	= 60.00		
Mountain RS end of link		Forest RS en	Forest RS end of link	
Latitude	00 00 30.40 N	Latitude	00 42 24.00 S	
Azimuth	137.83 degrees	Azimuth	317.83 degrees	
Elevation	1058 metres ASL	Elevation	344 metres ASL	
Antenna CL	8.1 metres AGL	Antenna CL	48.3 metres AGL	
Antenna CL	o.1 illeties AdL	Afficentia CL	48.3 Illettes AGL	

RESULTS

The 106 km link provides ANDESPETRO with a total capacity of 2872 kbit/s, allocated to an E1 and 784 kbit/s Ethernet. The quality of service has remained at 99.999% availability. Perhaps most importantly, using the Aprisa XE provided ANDESPETRO with a cost-effective solution to their communications problems.

ABOUT 4RF COMMUNICATIONS

Operating in more than 120 countries, 4RF Communications provides radio communications equipment for critical infrastructure applications. Customers include utilities, oil and gas companies, transport companies, telecommunications operators, international aid organisations, public safety, military and security organisations. 4RF point-to-point and point-to-multipoint products are optimized for performance in harsh climates and difficult terrain, supporting IP, legacy analogue, serial data and PDH applications.

Copyright © 2011 4RF Communications Limited. All rights reserved. This document is protected by copyright belonging to 4RF Communications Limited and may not be reproduced or republished in whole or part in any form without the prior written consent of 4RF Communications Limited. While every precaution has been taken in the preparation of this literature, 4RF Communications Limited assumes no liability for errors or omissions, or from any damages resulting from the use of this information. The contents and product specifications within it are subject to revision due to ongoing product improvements and may change without notice.



"

The use of sub 3 GHz spectrum overcame the propagation problems encountered in areas of forest, mountains and tropical environments, to provide a 99.999% quality of service link providing an E1 and Ethernet communications between the two locations.

"



For more information please contact EMAIL sales@4rf.com URL www.4rf.com